

**Manufacturer:**

Thrane & Thrane A/S
Lundtoftegaardsvej 93 D
DK-2800 Kgs. Lyngby
DENMARK

Tel: + 45 39 55 88 00
Fax: + 45 39 55 88 88
<mailto:info@thrane.com>

Antenna model:

SAILOR 900 VSAT 407009B-00500
and 407009E-00500

Antenna aperture dimensions:

1.03 m

Standard:

M

Characterization date:

30-04-2013

Last update:

19-01-2017

System Description:

Stabilised maritime antenna – ring focus Gregorian configuration – Sandwich foam pre-preg layers radome. Three axis stabilization platform with conical RF tracking.

BUC 407009B-0500 NextGenWave 8W rating
407009E-0500 NextGenWave 20W rating

LNB Philtech
OMT Thrane & Thrane TT 60-131011

Models Characterized:

Standard configuration: linear orthogonal polarization with co-polarized or cross-polarized signal reception option.

Maximum Allowed EIRP:

For digital carriers transmitted at the satellite receive contour of 0 dB/K (EESS 502 refers):

39.8 dBW / 40 kHz for an orbital separation of the adjacent satellite $\geq 2.5^\circ$

39.6 dBW / 40 KHz for an orbital separation of the adjacent satellite $\geq 2.0^\circ$

35.6 dBW / 40 kHz for an orbital separation of the adjacent satellite $\geq 1.5^\circ$

Tx Frequency:

13.75 – 14.50 GHz

Rx Frequency:

10.70-12.75 GHz

Tx Gain:

41.1 dBi (typical at 14.25 GHz)

Rx Gain:

40.2 dBi (typical at 11.7 GHz)

Tx XPD:

>30 dB within -1 dB contour

Rx XPD:

>30 dB within -1 dB contour

G/T (measured with radome)

19.9 dB/K @ 12.75 GHz 30 ° Elevation

Remarks:

1-The manufacturer states that the RMS pointing error is less than 0.20° for the following ship motions:

Roll = 30° in a period of 6 sec

Pitch = 15° in a period of 4 sec

Yaw = 10° in a period of 10 sec

2-The RF performance characterization was performed on one antenna unit with radome, at the France Telecom test range of La Turbie, France on the 18-20 April 2013.

3-Thrane & Thrane has inserted in the ACU software a look-up table with the polarization skew of the Eutelsat satellites, to protect against the mishandling of polarization skew values by installers.

4-The characterization's validity is subject to regular submission of patterns to confirm that the system remains compliant with the Eutelsat standards.

Restrictions:

The use of Rx band 10.7 to 10.95 GHz may be subject to impairments because the isolation of the sidelobes at 3° from the boresight is less than 20 dB at 10.70 GHz (17.8 dB). Nevertheless these operations may be exceptionally authorized according to a valid Eutelsat transmission plan.